



FUNG YUAN Sincere / Innovation / Profession / Responsibility / Enthusiasm


搭接式 收縮包裝機

FYT-501

Automatic Tray Shrinker (Overlap)



包裝範例 Samples



鋒源機械有限公司

FUNG YUAN MACHINERY CO., LTD.

公司：台中市豐原區國環北路二段321號

工廠：台中市豐原區東北街187號

Office : No.321, Sec.2, Yuan Hwan North Rd., Feng Yuan Dist., 420 Taichung City, Taiwan

Factory : No.187, Tung Pei St., Feng Yuan Dist., Taichung, Taiwan

TEL : 886-4-25232986, 25227318, 25253217-8 FAX : 886-4-25276828

Http : //www.fungyuan.com E-mail : fungyuan@ms25.hinet.net

FYT-501 搭接式收縮包裝機 Automatic Tray Shrinker (Overlap)

特點:

- FYT-501系列機型採用目前市場上最流行的搭接式包裝方式，速度快、精準確、多功能、低維修、易操作、省力化。
- 包裝材料PE收縮膜，透明及彩色定位版膜均適用。
- 單片式膠膜包裝，於產品底部搭接，無封口線收縮包裝。
- 電腦多軸程控，彩色人機介面操作，更換規格、尺寸、長度、高度於介面，操作簡易。
- 機械每一個動作及工作站均可顯示於螢幕上檢視。
- 送膠膜伺服器馬達，傳動長短易控制，真空吸盤輸送裝置。
- 單軸氣壓式膠膜架，兩組互換使用，每組可承受60Kgs~90Kgs重量膠膜。
- 繞膠膜機構伺服器馬達控制，不同包裝高度可隨時提供動作服務，故障自動跳脫裝置，刀口式輸送機。
- 包裝機可配合生產線，前、後連鎖控制系統。
- 機台SS41鋼材，粉體烤漆處理；內爐SUS#304不銹鋼材製造。
- 電熱不銹鋼電熱管外加散熱片、兩端陶瓷接頭線、溫度可調整、保溫層石棉岩保溫。
- 收縮爐內風循環式，風量角度可調節式，雙循環式。
- 機架方型鋼管焊接成型，SS41鋼材，粉體烤漆處理。

FYT-501 規格表 / FYT-501 SPECIFICATION :

規格 Specification	機型 Model	FYT-501 搭接式收縮包裝機 FYT-501 Automatic Tray Shrinker (Overlap)	
項目 Item		包裝機 Overlapping Machine	收縮機 Shrinking Tunnel
電源 Voltage		220V or 380V x 3PH ; 50-60 Hz	220V or 380V x 3PH ; 50-60 Hz
馬力 Hp		6 HP	2 HP
電熱 Heat			32 KW
空壓源 Air Consumption		5~6 kgf / cm ² 100n l / min	
包裝能量 Packing Speed		25 ~ 30 包 / 分 packs / min	5 ~ 25 公尺 / 分 M / min
適用膠膜 Shrink Film (LDPE)		PE 透明或彩色印刷膜 Transparent or printed film	PE 透明或彩色印刷膜 Transparent or printed film
有效包裝尺寸 Packing Size		(L x W x H) (Unit:mm) 300~420L x 200~400W x 140~330H	(L x W x H) (Unit:mm) MAX: 420L x 400W x 350H
機械尺寸 Machine Dimension (LxWxH)		2800Lx1190Wx1450H (Unit:mm)	2800Lx1330Wx1810H (Unit:mm)
工作輸送高度 Operation Height		1050±50 mmH	1050±50 mmH
機械重量 Machine Weight		1000 kgs	900 kgs

Features:

- FYT-501 series are our newly developed models that meet the newest over-lap packaging systems adopted by the industries in the world. High speed, Nice packing, Functional, Simple maintenance, easy operation and manpower saving.
- Packing material is LDPE shrink film. Both transparent and printed shrink film can be used.
- Single film packing is overlapped at the bottom of the products, there are no heat seals on the packages.
- Multi-Axis of PC base programming control by color touch screen operation. Within specified range (L x W x H) for different products is completely simple for size-change on the screen.
- Each action and workstation of machines can be displayed on the screen for view.
- Film is delivered by Servo motor, so the film length is easily controlled. Sucking conveyor is equipped.
- Two film cradles of single-spindle air pressure can be exchanged. Each set can bear 60 ~ 90kgs of film roll.
- Film-rolling mechanism is controlled by Servo motor, the packing in different heights can proceed at any time. Automatic trip device for breakdown and lip type conveyor are also equipped.
- The machine can match the interlocking control system of before/after production lines.
- The machine body is made of standard steel #SS41 with powder painted surface. Inner oven is made of SUS#304.
- Electric heating stainless steel tube is equipped with fin and installed with ceramic adapter wires at two ends, so temperature can be adjusted. ABM Mineral Wood board covers heat-reserving layer.
- Twin circulation fans are to ensure even heat distribution inside shrink oven. Heat wind direction is adjustable.
- The machine's structure is melted and formed with square SS41 steel pipes with powder painted surface.

機械外觀尺寸圖 / M/C Dim. Illustration

單位 / mm

